APPLICA	BLE STAN	DARD								
OPERATING TEMPERATURE RANGE VOLTAGE CURRENT		RE RANGE	-35 °C TO 85 °C (NOTE	ES 1) T	STORAGE EMPERATU		SE .	−10 °C TO 60 °C		
			00 1/ 40		APPLICABLE CONNECTOR			DF37*-44DS-0.4V		
			0.3 A							
SPECIFICATIONS										
l-	ГЕМ		TEST METHOD			F	REQU	IREMENTS	QT	АТ
CONSTR	RUCTION				•					
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCOF	ACCORDING TO DRAWING.				
MARKING		CONFIRM					Х	X		
ELECTRIC CHARA										
CONTACT RESISTANCE		20 mV AC OR LESS 1khz,1m A .			100 mΩ	100 mΩ MAX.				_
INSULATION RESISTANCE		100 V DC.			50 MΩ MIN.				X	1-
VOLTAGE PROOF		100 V AC FOR 1 min.			NO FLA	NO FLASHOVER OR BREAKDOWN.				1_
MECHANICAL CHA		⊥ \RACTI	ERISTICS						X	
MECHANICAL OPERATION		500 TIMES INSERTIONS AND EXTRACTIONS.			2 NO	① CONTACT RESISTANCE: $100 \text{ m}\Omega$ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.				_
COUN	IT D	ESCRIPTI	ON OF REVISIONS	DE	SIGNED			CHECKED	DA	\TE
\triangle										
REMARKS		ERATURE RISING BY CURRENT				APPRO	-	MO. ISHIDA	+	0. 24
						CHECK DESIGN	-	TS. MIYAZAKI NY. YAMASHIRO	+	10. 24 10. 24
Unless otherwise specified, refe					DRAV		VN	KR. AJITO 14. 10		10. 23
Note QT:Qualification Test AT:As					DRAWING NO.			ELC4-338056-01		
HS		SPECIFICATION SHEET			PART NO.		DF37CJ-44DP-0. 4V (53) CL684-3091-5-53			
I HIR		OSE ELECTRIC CO., LTD.			DE NO.	CL	CL684-3091-5-53 🕰 1			